









## Drivematic Delight: Amazing highlights.

- Ride-on machine – The efficient helper for large-area cleaning jobs
- Compact dimensions and a tight turning circle – Perfect for elevators and tight corridors
- Extra quiet – Suitable for hospitals and retirement homes
- Sophisticated ergonomics and intuitive display – Easy to read and operate
- Simple tank cleaning – For optimized hygiene



### Silent: cleaning should be seen, not heard



Drivematic Delight comes with suction airflow insulation as standard. And the “Silent Kit” ensures absolute quiet.

This optional extra further reduces the noise emissions from your machine considerably – an important consideration in hospitals and retirement homes.

### Tank cleaning: Quick and hygienic



Value-retention begins with cleanliness – that also applies for your machine fleet. That is why Drivematic Delight comes with a custom service opening, via which the tank can be cleaned quickly and efficiently. Not only your cleaning results are improved: a clean machine will have a much improved service life.

### Dimensions: Can be used virtually anywhere



The compact ride-on machine measures only 85 cm in width, allowing it to fit comfortably in any elevator. Even those hard to reach checkout lanes pose no problem. Drivematic Delight is super agile, which means even the tightest passages can get a perfect clean.

# Models and Versions

Model	Drivematic Delight				Drivematic Delight Dosing			
	Standard	Silent	SDL	Silent SDL	Standard	Silent	SDL	Silent SDL
Article Number	50.092	50.093	50.094	50.095	50.096	50.097	50.098	50.099
<b>Basic Version</b>								
Internal charger	•	•	•	•	•	•	•	•
Electric drive system	•	•	•	•	•	•	•	•
Quick-fill system	•	•	•	•	•	•	•	•
Brush housing, complete	•	•	•	•	•	•	•	•
Suction nozzle, complete	•	•	•	•	•	•	•	•
Squeegee set	•	•	•	•	•	•	•	•
Dosage system, complete	–	–	–	–	•	•	•	•
<b>Optional Extras</b>								
Silent kit	–	•	–	•	–	•	–	•
Warning beacon (SDL)	–	–	•	•	–	–	•	•
<b>Technical Data</b>								
Theoretical area coverage	3960 m <sup>2</sup> /h				3960 m <sup>2</sup> /h			
Working width	66 cm				66 cm			
Total length	138 cm				138 cm			
Machine width	68 cm				68 cm			
Suction width	85 cm				85 cm			
Total height	117 cm				117 cm			
Weight (incl. batteries)	335 kg				335 kg			
Weight (incl. batteries + water)	405 kg				405 kg			
Fresh water tank	70 l				70 l			
Recovery tank	80 l				80 l			
Number of brushes	2 pcs				2 pcs			
Brush pressure	40 kg (0,36 N/cm <sup>2</sup> )				40 kg (0,36 N/cm <sup>2</sup> )			
Brush speed	180 1/min				180 1/min			
Brush motor output	1100 W				1100 W			
Vacuum	110 mbar				110 mbar			
Airflow rate	32 l/s				32 l/s			
Forward speed	0-7 km/h				0-7 km/h			
Backward speed	0-2.5 km/h				0-2.5 km/h			
Battery capacity	105/180 Ah				105/180 Ah			
Battery life	up to 3,5 h				up to 3,5 h			
Suction turbine output	350 W				350 W			
Drive type	Drive motor				Drive motor			
max. working incline	12%				12%			
Total output	2240 W				2240 W			
Drive system output	750 W				750 W			
Noise level	63/59 dB				63/59 dB			



See the Drivematic Delight  
Wetrok in action.



**Wetrok AG** Steinackerstrasse 62, 8302 Kloten  
Phone +41 43 255 51 51, Fax +41 43 255 53 79

**Wetrok Austria GmbH** Kolpingstrasse 18, 1230 Wien  
Phone 0800 20 48 68, Fax 0800 20 48 78

**Wetrok GmbH** Maybachstrasse 35, 51381 Leverkusen  
Phone +49 2171 398-0, Fax +49 2171 398-100

**Wetrok Polska S.A.** ul. Łączyny 4, 02-820 Warsaw  
Phone +48 22 331 20 50, Fax +48 22 331 20 60

**Wetrok AB** Bergkällavägen 32, 192 79 Sollentuna  
Phone +46 8 444 34 00, Fax +46 8 444 34 01

[www.wetrok.com](http://www.wetrok.com)

