
HS R 130/ADM



Ride-on sweepers

The HS R 130 is the ride-on sweeper ideal for cleaning large areas. It guarantees excellent performance with a productivity of 9700 m²/h and a cleaning width of 1300 mm due to its centre and side brushes. Depending on the type of dirt to be removed, the operator can adjust the pressure of the central brush using a practical lever. In addition, the pedal-operated lifting of the central flap allows the picking up of materials and small objects. While working, the dust is retained by a powerful filter system consisting of 8 cartridge filters with electric filter shaker, allowing the operator to work in complete safety. The HS R 130 ADM model is equipped with the practical automatic tipping system, operated via the control panel, which allows the collection container to be lifted and emptied directly into the waste bin quickly and easily. The impact-resistant steel frame and certified antistatic system make the HS R 130 a robust and safe machine. The BC version has batteries (24V) and a battery charger on board.





CONTROL PANEL PRACTICAL AND INTUITIVE



90° STEERING ANGLE (2 MT)



SIDE BRUSH LIFT LEVERS



BRAKE PEDAL AND PARKING BRAKE



ADM: AUTOMATIC TILTING SYSTEM. MAXIMUM UNLOADING HEIGHT 145 CM



ADJUSTABLE, ERGONOMIC AND ENVELOPING SEAT



FRONT LIGHTING



BLINKING LIGHT

and a battery charger on board.

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
HS R 130	10.8130.00	1
HS R 130 ADM	10.8133.00	1
HS R 130 BC	13.8130.00	1
HS R 130 BC ADM	13.8133.00	1

Main brush cleaning width + right side brush + left side brush	mm	780	- 1025 - 1270
Productivity	m²/h	970	0
Power supply		Bat	tery 24V
Installed power	W	254	0
Advancement		Wit	h traction
IP code		IPX)
BATTERIES			
Туре	Battery set (4 pcs) 6V 240Ah (*)		
Running time	h-n	nin	2 h and 30 min
Battery compartment dimensions x No	mm	x No	810x335x360 X
BRUSHES			
Main brush length x No	mm>	<no< td=""><td>780 x 1</td></no<>	780 x 1
Side brush diameter x No	mm	x No	500×2
Main brush motor	W		900
Right side brush motor	W		90×2
TRACTION			
Motor rating	W		1200
Driving speed	km/ł	٦	7,5
Hill climbing ability	%		20

VACUUM AND DUST FILTERING SYSTEM

Motor rating	W	260
Noise level	dB(A)	75
Filter type - Material x No		Cartridge - Polyester x 8
Filtering surface - Dust Filter shaker	m²	6,4 - Electric
Waste container: position - emptying - capacity	Rear - Manual / Automatic (**) - 115 I	
Weight (without batteries)	Kg	375 / 448 (**)
Dimensions	mm	1550x1270x1340/

1630×1270×1300 (**)

STANDARD ACCESSORIES

TYPE	REF. NO.
Polypropylene main brush	40.0264.00
Polypropylene side brush (***)	40.0265.00
Polyester cartridge filter (****)	39.0329.00
Electric filter shaker	
Liftable flap	
Gel battery set (4 pcs) 6V 240Ah (*)	22.0835.00
On board charger 24V 30A (*)	18.0089.01

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Mixed steel main brush	40.0266.00
Mixed steel side brush	40.0267.00
HEPA filter	39.0330.00
Front dust conveyor	39.0331.00
Protective roof	39.0332.00
Main carpet brush	40.0268.00

(*) For BC version (**) ADM version (***) 2 brushes on standard equipment (****) 8 on standard equipment